

Specifications	T55	T75	T90	T115	T135	
<b>BTUs</b> <small>(water temp/ambient air/ relative humidity)</small>	80/80/80	52,000	74,000	96,000	112,000	132,000
	80/80/63	50,000	70,000	90,000	106,000	125,000
	80/50/63	33,000	49,000	65,000	74,000	84,000
<b>C.O.P.</b> <small>Coefficient of Performance (water temp/ambient air/ relative humidity)</small>	80/80/80	6.0	5.6	6.0	5.6	5.7
	80/80/63	5.8	5.4	5.8	5.4	5.6
	80/50/63	4.0	4.0	4.2	4.0	4.0
<b>Refrigerant</b>	R410A	R410A	R410A	R410A	R410A	
<b>Heat Exchanger</b>	Tube in Tube	Tube in Tube	ThermoLink®	ThermoLink®	ThermoLink®	
<b>Electrical</b>	kW Input	2.7	3.9	4.7	5.9	6.8
	Voltage/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
	Min. Circuit Ampacity	19.1	26.8	40.2	38.2	43.3
	Max. Fuse Size	30	45	60	60	60
<b>Water Flow</b>	Min./Max. (gpm)	20/45	20/45	30/70	30/70	30/70
A Heater Bypass Kit is required when flow rates exceed the maximum						
<b>Physical</b>	Weight (lbs)	180	200	255	259	287
	Length x Width x Height (in)	34" x 34" x 28"	34" x 34" x 28"	34" x 34" x 39"	34" x 34" x 39"	34" x 34" x 39"
<b>Shipping</b>	Weight (lbs)	220	240	305	309	337
	Length x Width x Height (in)	38" x 36" x 33"	38" x 36" x 33"	38" x 36" x 43"	38" x 36" x 43"	38" x 36" x 43"
Rated in accordance with AHRI standard 1160 water temp/ambient air/relative humidity Specifications subject to change						